

Amendments to the Claims:

A listing of the entire set of pending claims (including amendments to the claims, if any) is submitted herewith per 37 CFR 1.121. This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1.(Previously Presented) A mercury-free gas discharge lamp comprising:
an inner vessel including electrodes for providing a discharge arc; and
an outer bulb, wherein a surface of at least one of the inner vessel and the outer bulb comprises a pattern configured to increase a diffuseness of the discharge arc, wherein the pattern includes structured arrangements formed on the surface, the structured arrangements physically overlapping over each so that a first structured arrangement is in physical contact with a second structured arrangement.

2.(Previously Presented) The mercury-free gas discharge lamp as claimed in claim 1, wherein the pattern is configured to increase the diffuseness of the discharge arc of the mercury-free gas discharge lamp by 0.01 mm up to 1.5 mm in comparison with a corresponding gas discharge lamp without the pattern.

3.(Previously Presented) The mercury-free gas discharge lamp as claimed in claim 1, wherein the pattern is configured to reduce the discharge arc curvature of the mercury-free gas discharge lamp by 0.01 mm up to 0.5 mm in comparison with a corresponding gas discharge lamp without the pattern.

4.(Previously Presented) The mercury-free gas discharge lamp as claimed in claim 1, wherein the mercury-free gas discharge lamp is at least one of a mercury-

free high-pressure gas discharge lamp, and a mercury-free xenon high-pressure gas discharge lamp.

5.(Previously Presented) The mercury-free gas discharge lamp as claimed in claim 1, wherein light losses of the mercury-free gas discharge lamp as compared with a gas discharge lamp without the pattern amount to ≤ 90 lumens and ≥ 5 lumens.

6.(Previously Presented) The mercury-free gas discharge lamp as claimed in claim 1, wherein the at least one of the inner vessel and the outer bulb is made of at least one of glass and ceramic materials.

7.(Previously Presented) The mercury-free gas discharge lamp as claimed in claim 1, wherein the at least one of the inner vessel and the outer bulb has the pattern at least one of on its outer surface facing away from the discharge arc, on its outer surface facing the discharge arc, and within the inner vessel or bulb material.

8.(Previously Presented) The mercury-free gas discharge lamp as claimed in claim 1, wherein the pattern is formed by at least one of a laser treatment, sandblasting, surface etching, surface slitting and roughening, and is optionally finished by fire polishing.

9.(Previously Presented) The mercury-free gas discharge lamp as claimed in claim 1, wherein the pattern covers a surface area of 2 mm² to 12 mm², said surface area being arranged over a brightest spot in the discharge arc.

10.(Previously Presented) The mercury-free gas discharge lamp as claimed in claim 1, wherein the mercury-free gas discharge lamp is configured for motor vehicles.

11.(Previously Presented) The mercury-free gas discharge lamp of claim 1, wherein the pattern is further configured to provide an optical impression when viewed from an exterior of the mercury-free gas discharge lamp, the optical impression showing a change in a viewed position of a brightest spot of the discharge arc despite lack of an actual change of an actual position of the brightest spot within the mercury-free gas discharge lamp.

12.(Previously Presented) The mercury-free gas discharge lamp of claim 1, wherein the pattern is further configured to not change an actual position of a brightest spot of the discharge arc and yet provide an optical impression showing a perceived change in a perceived position of a brightest spot when viewed from an exterior of the mercury-free gas discharge lamp.

13.(Previously Presented) The mercury-free gas discharge lamp of claim 1, wherein the pattern includes at least one of lines, dots, circles, rectangles, and polygons.

14.(Previously Presented) The mercury-free gas discharge lamp of claim 13, wherein the lines includes at least one of straight, curved, wavy, and spiraling lines.

15.(Previously Presented) The mercury-free gas discharge lamp of claim 13, wherein the structured arrangements are at least one of same and different sizes, and are partly or fully planar in shape.

Claim 16 (Canceled)

17.(Previously Presented) The mercury-free gas discharge lamp of claim 1, wherein the structured arrangements are at least one of partly and fully planar.

18.(Previously Presented) A discharge lamp comprising:
an inner vessel including electrodes for providing a discharge arc; and
an outer bulb, wherein at least one of the inner vessel and the outer bulb
comprises a pattern configured to increase a diffuseness of the discharge arc,
wherein the pattern includes structured arrangements formed on the surface, the
structured arrangements being physically overlapping over each other so that a first
structured arrangement is in physical contact with a second structured arrangement.

19.(Previously Presented) The discharge lamp of claim 18, wherein the
pattern is further configured to provide an optical impression when viewed from an
exterior of the discharge lamp, the optical impression showing a change in a viewed
position of a brightest spot of the discharge arc despite lack of an actual change of
an actual position of the brightest spot within gas discharge lamp.

20.(Previously Presented) The discharge lamp of claim 18, wherein the
pattern is further configured to not change an actual position of a brightest spot of
the discharge arc and yet provide an optical impression showing a perceived change
in a perceived position of a brightest spot when viewed from an exterior of the
discharge lamp.

21.(Previously Presented) The discharge lamp of claim 1, wherein the pattern
includes homogeneously overlapping rings arranged in at least one of row and
columns formed by at least one of a laser treatment, sandblasting, surface etching,
surface slitting and roughening.

22.(Previously Presented) The discharge lamp of claim 18, wherein the
pattern includes homogeneously overlapping rings arranged in at least one of row

and columns formed by at least one of a laser treatment, sandblasting, surface etching, surface slitting and roughening.